

**PC CABLES**



**FLOPPY-ROUND**

Flexible PVC pipe for added shielding and wiring protection to meet the demand of cooling in space-limited servers & high performance systems. These space-saving PVC cables reduce clutter inside the case, which adds more airflow for cooling.

**FLOPPY-ROUND 18"**



**ATA ROUND CABEL**

Our rounded IDE cables are ATA 66/100/133 compliant and backwards compatible with Ultra33, IDE/ATAPI hard drives, tape drives, zip drives, LS-120s and other IDE/ATAPI devices.

18 INCH (gray,blue)      24 INCH(gray,blue,red,yellow)      36 INCH(gray,blue,red,yellow)

<b>ATA-100R-18</b>	<b>ATA-100R-24</b>	<b>ATA-100R-36</b>
<b>ATA-100R-18-BL</b>	<b>ATA-100R-24-BL</b>	<b>ATA-100R-36-BL</b>
	<b>ATA-100R-24-RD</b>	<b>ATA-100R-36-RD</b>
	<b>ATA-100R-24-YL</b>	<b>ATA-100R-36-YL</b>



**IDE CABLE FOR HARD DRIVE**

40-pin x 3connector, Dual connection allows you to connect 2 or 3 IDE (40 pin) devices. Connecting IDE devices to a main board.

<b>4018FK-3 18" 3x40</b>	<b>4036FK-3 36" 3x40</b>
<b>4024FK-3 24" 3x40</b>	<b>4018FK-2 18" 2x40</b>



**IDE CABLE FOR HARD DRIVE ATA**

40-pin x 3 connector (80-conductor). 3 connectors for 2 devices. This cable will work with ATA133/ATA100/ATA66 hard drive. The cable is recommended for any particular application allowed.

<b>4018FK-3ATA 18" 3x40</b>	<b>4036FK-3ATA 36" 3x40</b>
<b>4024FK-3ATA 24" 3x40</b>	<b>4018FK-2ATA 18" 2x40</b>

**FLAT CABLE**

These cables are used for building internal PC cabling to support floppy and hard drives. Built with 28 AWG primaries and jacketed with PVC, this cable is suitable for use with any industry standard .050-centerline IDC connectors, UL.



100FT ROLL	500FT ROLL
<b>FLAT-10-100</b>	<b>FLAT-10-500</b>
<b>FLAT-20-100</b>	<b>FLAT-16-500</b>
<b>FLAT-25-100</b>	<b>FLAT-20-500</b>
<b>FLAT-34-100</b>	<b>FLAT-26-500</b>
<b>FLAT-40-100</b>	<b>FLAT-34-500</b>
<b>FLAT-50-100</b>	<b>FLAT-40-500</b>