



**AUDIO VIDEO CABLES**

**BNC CABLE**

Low loss coaxials are particularly suitable for transmission of RGB signals over extended distances without worry of signal deterioration or crosstalk. 26 AWG 75 Ohm, Black PVC. Fully braided shield, UL.

Male-to-Male

- 5BNC-5BNC-03** 3'
- 5BNC-5BNC-06** 6'
- 5BNC-5BNC-12** 12'
- 5BNC-5BNC-25** 25'
- 5BNC-5BNC-50** 50'
- 5BNC-5BNC-75** 75'
- 5BNC-5BNC-100** 100'

Male-to-Male

- 3BNC-3BNC-03** 3'
- 3BNC-3BNC-06** 6'
- 3BNC-3BNC-12** 12'
- 3BNC-3BNC-25** 25'
- 3BNC-3BNC-50** 50'
- 3BNC-3BNC-75** 75'
- 3BNC-3BNC-100** 100'



**HD15 TO 5BNC**

High-end monitors require high-end monitor cables. DB15HD to BNC monitor cable controls each color & sync individually for optimum results. PVC BLACK, High Density 15pin D-SUB Male Connector Molded Hood w/ Thumbscrew Color Coded. Fully shielded, UL.

Male-to-Male

- M15BNC5-06** 6'    **M15BNC5-25** 25'
- M15BNC5-10** 10'    **M15BNC5-35** 35'
- M15BNC5-15** 15'    **M15BNC5-50** 50'



**HD15 TO 5BNC BREAKOUT**

This low-loss breakout assembly features a High Density 15 pin D-Sub male on one end and five, 75ohm female BNC's on the other end. Just plug the HD15 male into your equipment or wall plate and connect a 5-channel BNC cable to the other end and you are all set to run high-resolution video. Easily mounts in a wall plate or panel. PVC Black, 26AWG, UL.

Male-to-Female

- B5R-HD15-FM-6IN** 6 inch
- B5R-HD15-FM-01** 1'
- B5R-HD15-FM-03** 3'
- B5R-HD15-FM-06** 6'

